



TRE Printer

- High printing speed: 30 – 35 mm/sec
- Power Supply: 9 – 16V
- Easy paper change (Auto load)
- Paper and sensor
- ESC/POSTM emulation
- Standard international characters font
- Standard line printing with auto feed
- Two dimension font scaling
- Print Density
- Online device checking
- Graphic image mode for bitmap printings
- Load Logos into printer memory (average logo size 3 Kb each)
- Available memory for logo's storage (30 Kb)
- Print selected logo command
- RS232 or TTL serial interface (2400 - 19200 bps)



MSR Integrated Printer

- Small-sized portable and desk-top configuration
- Easy paper load by clamshell units
- One(1)hour continuous printing with rechargeable battery
- Auto online mode
- High speed printing
- Bit image graphic
- 32kbyte buffer
- IrDA interface
- Support for many bar code types(JAN/EAN-8,JAN/EAN-13,CODE39,CODE128,CODE93)
- 2 Track MSR Integrated



Handy 700 Printer

- Small-sized portable and desk-top configuration
- Easy paper load by clamshell units
- One(1)hour continuous printing with Lit-ion battery
- Programming by front button
- Auto online mode
- High speed printing
- Bit image graphic
- 128 Kbyte buffer
- IrDA interface
- Support for many bar code types(JAN/EAN-8,JAN/EAN-13,CODE39,CODE128,CODE93)