

Hyper Wide Dynamic Box Camera (Effio WDR III)

MTC-WD116EF
MTC-WD116MEF

MTC-WD116EF, MTC-WD116MEF



FEATURES




Mechanical IR Cut Filter (ICR)
MTC-WD116MEF



Sony Effio WDR III
700TVL

MTC-WD116EF, MTC-WD116MEF

- ◆ 1/3" Hyper Wide Dynamic Color Camera (Sony Effio-P WDR III)
- ◆ Color:680TVL, B/W:700TVL
- ◆ Color:0.03Lux@F1.2, B/W:0.01Lux@F1.2, Sense-up:0.0001Lux@F1.2
- ◆ Powerful 1024X WDR (60dB)
- ◆ Multi-Language OSD Control / RS485 Control
- ◆ 196 Step Shutters (4 Schedule Shutter, Time&Speed Adjustable)
- ◆ Fog Reduction ; High Light Compensation (HLC)
- ◆ Digital Image Stabilizer (DIS)
- ◆ 2D/3D Noise Reduction ; Sense Up (512x) Functions
- ◆ E-zoom Function (1~256x)
- ◆ Motion Detection Function ; Mosaic Privacy Mask
- ◆ Timer Clock



12Vdc/24Vac
Tol:±0.5 Unit:mm

SPECIFICATIONS

	MTC-WD116EF		MTC-WD116MEF	
	PAL	NTSC	PAL	NTSC
TV System	PAL	NTSC	PAL	NTSC
Image Sensor	1/3" Sony 960H Double-speed (Double-density) CCD			
Number of Total Pixels (CCD)	1028(H)x596(V)	1028(H)x508(V)	1028(H)x596(V)	1028(H)x508(V)
Resolution ; DSP	Color:680TVL, B/W:700TVL ; Sony Effio-P (WDR III)			
Minimum Illumination	Color:0.03Lux@F1.2, B/W:0.01Lux@F1.2, 0.005Lux@F1.2 (with ICR), Sense-up:0.0001Lux@F1.2			
Wide Dynamic Range	1024X Normal Camera (60dB)			
Video Output	1.0Vp-p Composite, 75Ω (BNCx2)			
Signal to Noise Ratio (S/N)	More than 55dB (AGC off)			
Gamma Correction	0.45			
Mechanical IR Cut Filter (ICR)	NA		Automatically Switches (Switching Lux Level can be adjusted)	
IR LED ; Working Distance	NA		Compatible with Infrared Illuminator	
Menu	OSD Control or by RS485 Control			
Title	TITLE (LOCATION)			
Synchronizing System	INTERNAL / LINE LOCK (AC Version Only)			
Day&Night Mode	COLOR / B&W / AUTO / DAY&NIGHT SCHEDULE / EXT			
Electronic Shutter	AUTO: 1/50(60)~1/100,000 sec. / 4 SCHEDULE SHUTTER (Time&Speed Adjustable) (196 Steps, 1/50~1/2000 sec.) MANUAL: 196 Steps, 1/50, 1/60, 1/70, 1/80, 1/90, NTSC FL 1/100, 1/110, PAL FL 1/120, 1/130, ... ,1/1980, 1/1990, 1/2000 sec.			
Automatic Gain Control	0~200 Levels (Adjustable Level Settings)			
White Balance	ATW / AWB / PUSH LOCK / MANUAL / 3200K / 6300K / ANTI CR			
WDR ; BLC ; Fog Reduction	WDR / BLC / FOG /OFF			
High Light Compensation	ON / OFF / AUTO			
Digital Image Stabilizer (DIS)	ON / OFF			
Dynamic Noise Reduction	3D / 2D			
Sense Up	AUTO (Limit x2~x512) / OFF			
Language	ENGLISH / TRADITIONAL CHINESE / SIMPLIFIED CHINESE			
Image Setting	SHARPNESS / CONTRAST / SATURATION / HUE / MIRROR			
E-Zoom	x1~x256, Pan / Tilt Adjustable			
Motion Detection ; Privacy	ON / OFF (24x16 Zones, Alarm) ; ON / OFF (15 Zones Programmable, Quadrangle Mosaic)			
Timer Clock	Year/Month/Date, Hour/Minute/Second			
Camera Control Interface	RS485 Interface OSD Control by Pelco-D, Pelco P			
Automatic IRIS ; Connector	VIDEO / DC ; D4 IRIS Jack			
Lens Mount	CS / C mount (With Adaptor Ring)			
Lens, Angle of View (H)	Lens Option: Please See the Page of Lens Series			
Water Resistance	NA			
Max. Breaking Strength	NA			
Power Supply ; Consumption	12Vdc/24Vac (10.8~39Vdc/24Vac) ; 2.5W			
Operation ; Storage Temp.	-10°C~50°C ; -20°C~60°C			
Operation ; Storage Humidity	Maximum: RH80% ; RH90%			
Dimensions	67(W)x56(H)x120(L)mm			
Net Weight	350g			
Accessories Option	Lens:SHV-IR2812DAI, SHV-IR3085DAI, SHV-IR7550DAI			

*Specifications are unfixed and do not apply to customized projects. 130508