



FB3027



The 3-megapixel FB3027 bullet IP camera is outfitted with an IP67-rated housing, making it an excellent choice for outdoor applications. The FB3027 supports day / night functionality via the built-in mechanical ICR. Adjustable IR LED illuminators allow the camera to capture clear images even in low lighting environments. The FB3027 features vari-focal lens, Wide Dynamic Range (WDR), Digital Noise Reduction (DNR), Smart Stream and ROI (Region of Interest) for bandwidth / storage optimization.



features




3-megapixel



waterproof & dustproof



low temp. protection



adjustable IR LEDs



Smart Stream

key features

- 3-megapixel 1/2.5" CMOS sensor with vari-focal lens (f=2.8~12mm)
- supports up to 2048 x 1536 at 20fps, 1920 x 1080 at 30fps
- H.264 / MJPEG / MPEG-4 compression (tri-codec)
- supports plug and play feature with AVer DVRs/NVRs
- robust housing with IP67 rating
- protection against low temperatures (-25°C)
- supports Quick Focus for quick and precise focus adjustment, works via a BNC monitor or via the camera's GUI
- built-in mechanical ICR (IR-cut filter removable) and adjustable Osram IR LEDs (30m) for excellent day and night visibility
- supports Wide Dynamic Range (WDR) and Digital Noise Reduction (DNR) to deliver cleaner, sharper images in challenging light environments

- supports Smart Stream and Region of Interest (ROI) and Event Booster technology, allowing for smart bandwidth / storage optimization through targeted image capturing
- EN50130-4 certified, ensuring high surge and electro-thermal resistance
- local storage backup (microSDHC/SDXC card, up to 64GB) when an event is triggered or the network is down
- event trigger actions: mail, FTP, save to memory card, relay, Samba
- NXU Lite video management software (free up to 32CH)

specs

model	FB3027
application environment	
indoor / outdoor	indoor / outdoor
weatherproof	IP67
vandal-proof	-
day / night control	auto / manual / schedule
camera image	
sensor	1/2.5" CMOS
min. illumination	color: 1 lux @ F1.4 black & white: 0.15 lux @ F1.4 0 lux @ F1.4 (IR LED on)
built-in IR LEDs	yes - adjustable strength (Osram)
IR distance	30m
mechanical ICR	yes
auto iris	yes
lens	
lens type	vari-focal lens
F/no	F1.4
focal length	f=2.8~12mm
angle of view	97° (W) ~ 28.7° (T) (horizontal) 61.2° (W)~ 21.6° (T) (vertical)
video	
compression	H.264 / MPEG-4 / MJPEG simultaneously
max. resolution (H.264 / MJPEG)	2048 x 1536
max. frame rate	H.264 / MJPEG up to 20fps (2048 x 1536) H.264 / MJPEG / MPEG-4 up to 30fps (1920 x 1080)
streaming	H.264 / MPEG-4 / MJPEG
multiple streams	yes
WDR (Wide Dynamic Range)	D-WDR
BLC (Backlight Compensation)	yes
DNR (Digital Noise Reduction)	2D, 2D/3D (dynamic)
Smart Stream	yes
ROI (Region of Interest)	yes

IMD (Intelligent Motion Detection) zone	3
privacy mask	3
image orientation	mirror, flip
audio	
audio encoder	G.711 / G.726 / AAC audio compression
audio streaming	2-way audio
microphone	external microphone input
network	
protocol	HTTP, HTTPS, TCP/IP (IPv4, IPv6), QoS, UPnP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, 3GPP (video only), Samba, SNMP(V1/V2c/V3), 802.1X
Ethernet	Ethernet (10/100 Base-T), RJ45 connector
security	password protection, IP address filtering, HTTPS encrypted data transmission
user	up to 10 users simultaneously
alarm	
trigger event	Event Booster, mail, FTP, save to memory card, relay, Samba
interface	
digital input / output	1 / 1
built-in storage option	microSDHC / microSDXC card (64GB max.)
general	
power supply	DC 12V / PoE
DC	power consumption 4.6W (IR LED off / heater off) 8.2W (IR LED on / heater off) 14.6W (IR LED off / heater on) 15.7W (IR LED on / heater on)
PoE	PoE Class 4 (IEEE802.3at) power consumption: 6.4W (IR LED off / heater off) 10.6W (IR LED on / heater off) 18.5W (IR LED off / heater on) 19.7W (IR LED on / heater on)
dimensions	82.2 W x 82.1 H x 200 D (mm)
net weight	1110g
temperature and humidity	-25°C ~ 45°C, 20% ~ 90%
other value-added features	Quick Focus, ePTZ, EN50130-4
software	

VMS	NXU Lite (free bundle up to 32CH)
supported languages	English, Arabic, Bulgarian, Czech, Danish, Dutch, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Simplified Chinese, Slovak, Spanish, Swedish, Thai, Traditional Chinese, Turkish

*specifications are subject to change without prior notice