



FD3020-M



The 3-megapixel FD3020-M dome IP camera, designed for indoor applications, provides excellent image quality under diverse lighting conditions. With built-in mechanical ICR and adjustable IR LED illuminators, FD3020-M can capture sharp images in low light and no light environments. Moreover, the camera is outfitted with a vast array of useful features including a motorized lens (MFZ), Wide Dynamic Range (WDR), Digital Noise Reduction (DNR), Smart Stream and ROI (Region of Interest) to optimize bandwidth / storage.




features




3-megapixel



**motorized
focus / zoom
(MFZ)**



**adjustable IR
LEDs**



Smart Stream



**Region of
Interest
(ROI)**

key features

- 3-megapixel 1/2.5" CMOS sensor with vari-focal lens (f=3~9mm)
- supports up to 2048 x 1536 at 20fps, 1920 x 1080 at 30fps
- H.264 / MJPEG / MPEG-4 compression (tri-codec)
- supports plug and play feature with AVer DVRs/NVRs
- motorized lens allows for easy focus and zoom adjustment (MFZ) directly via the camera's GUI
- built-in mechanical ICR (IR-cut filter removable) and adjustable Osram IR LEDs (30m) for excellent day and night visibility
- supports Wide Dynamic Range (WDR) and Digital Noise Reduction (DNR) to deliver cleaner, sharper images in challenging light environments
- supports Smart Stream and Region of Interest (ROI) and Event Booster technology, allowing for smart bandwidth / storage optimization through targeted image capturing
- EN50130-4 certified, ensuring high surge and electro-thermal resistance

- local storage backup (microSDHC/SDXC card, up to 64GB) when an event is triggered or the network is down
- event trigger actions: mail, FTP, save to memory card, relay, Samba
- NXU Lite video management software (free up to 32CH)

specs

model	FD3020-M
application environment	
indoor / outdoor	indoor
weatherproof	-
vandal-proof	-
day / night control	auto / manual / schedule
camera image	
sensor	1/2.5" CMOS
min. illumination	color: 0.8 lux @ F1.2 black & white: 0.1 lux @ F1.2 0 lux @ F1.2 (IR LED on)
built-in IR LEDs	yes - adjustable strength (Osram)
IR distance	30m
mechanical ICR	yes
auto iris	yes
lens	
lens type	motorized vari-focal lens
F/no	F1.2
focal length	f=3~9mm
angle of view	96.4° (W) ~ 31.7° (T) (horizontal) 69.6° (W) ~ 23.7° (T) (vertical)
bracket adjustment	pan: 280°, tilt: 30°~90°, rotation: 100°
video	
compression	H.264 / MPEG-4 / MJPEG simultaneously
max. resolution (H.264 / MJPEG)	2048 x 1536
max. frame rate	H.264 / MJPEG up to 20fps (2048 x 1536) H.264 / MJPEG / MPEG-4 up to 30fps (1920 x 1080)
streaming	H.264 / MPEG-4 / MJPEG
multiple streams	yes
WDR (Wide Dynamic Range)	D-WDR
BLC (Backlight Compensation)	yes
DNR (Digital Noise Reduction)	dynamic, 3D, 2D
Smart Stream	yes

ROI (Region of Interest)	yes
IMD (Intelligent Motion Detection) zone	3
privacy mask	3
image orientation	mirror, flip
audio	
audio encoder	G.711 / G.726 / AAC audio compression
audio streaming	2-way audio
microphone	external microphone input
network	
protocol	HTTP, HTTPS, TCP/IP (IPv4, IPv6), QoS, UPnP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, 3GPP (video only), Samba, SNMP(V1/V2c/V3), 802.1X
Ethernet	Ethernet (10/100 Base-T), RJ45 connector
security	password protection, IP address filtering, HTTPS encrypted data transmission
user	up to 10 users simultaneously
alarm	
trigger event	Event Booster, mail, FTP, save to memory card, relay, Samba
interface	
digital input / output	1 / 1
built-in storage option	microSDHC / microSDXC card (64GB max.)
general	
power supply	DC 12V / PoE
DC	power consumption 13W (IR LED on) 5W (IR LED off)
PoE	PoE Class 3 (IEEE802.3af) power consumption: 14W (IR LED on) 7W (IR LED off)
dimensions	144.6 Ø x 113.4 H (mm)
net weight	770g
temperature and humidity	0°C ~ 45°C, 20% ~ 90%
other value-added features	MFZ, ePTZ, EN50130-4
software	
VMS	NXU Lite (free bundle up to 32CH)
	English, Arabic, Bulgarian, Czech, Danish, Dutch, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Norwegian,