

# SHANY

## 2.0 Megapixel 1080P IP IR Dome Camera (Outdoor) SNC-L226M


- 1/2.7" 2.0 Megapixel Progressive CMOS Sensor
- 1920(H)x1080(V) (1080P) ; H.264, MPEG4, M-JPEG
- 0.0001Lux (IR LEDs on at 2 Lux)
- Shutter Mode (Auto/Manual)
- Sense Up Function
- Image Setting Functions
- Support Multicast
- Support 12Vdc Power Input
- Support ONVIF 2.0

Entry Level




### Features

<b>Video</b>	Image Sensor	1/2.7" 2.0 Megapixel Progressive CMOS Sensor	
	Video Resolution/Frame Rate	1920x1080P@30fps (1080P) ;1280x1024@30fps, 1280x960@30fps, 1280x720@30fps, 720x480@30fps	
	Video Frame Rate	Up to 30fps for All Video	
	Video Compression	H.264, MPEG4, M-JPEG	
	Minimum Illumination	0.0001Lux (IR LEDs on at 2 Lux)	
	Digital Wide Dynamic Range	NA	
	Second Video Output	1.0Vp-p Composite, 75Ω (BNC)	
	Signal to Noise Ratio	More than 50dB (AGC off)	
	Mechanical IR Cut Filter	Automatically Switches (B/W Mode<2Lux, Color Mode>5Lux)	
	IR LED ; Working Distance	42 units (IR LEDs on<2Lux, IR LEDs off>5Lux) ; 20~25m	
	<b>Function</b>	Menu	Can Be Set Via Browser
		Day&Night Mode	Color / B&W / Auto / External
Auto Electronic Shutter		1/100,000 to 1/7.5 sec.	
Manual Electronic Shutter		1/7.5, 1/15, 1/30, 1/60, 1/100, 1/250, 1/500, 1/1,000, 1/10,000, 1/100,000 sec.	
White Balance		Auto_wide / Auto_normal / Sunny / Shadow / Indoor / Lamp / FL1 / FL2	
DNR ; Sense Up		NA ; Yes	
Language		English / Japanese / Chinese (Traditional, Simplified) / Russian / Hungarian / German / Persian / Spanish / Polish / Dutch	
Image Setting		Brightness / Contrast / Saturation / Sharpness / Hue / EV Compensation / AWB / Rotation / Exposure Mode / Exposure Priority / Gain Control / Auto IRIS / BLC	
Motion Detection		Yes	
Timer Clock		Yes	
Camera Control Interface		Pelco D, Pelco P, Customer	
<b>Network</b>		Browser	IE 8.0 or Above
		Ethernet	10/100M Auto Negotiation
		Bit Rate Transmission	64 up to 12,000 Kbps
		Supported Protocols	TCP, UDP, HTTP, SMTP, FTP, NTP, DNS, DHCP, PPPoE, ARP, UPnP, RTSP, RTP, SNMP, TRAP, Ethernet (RJ-45 Wired 10/100 Base-TX)
	Video Streaming	H.264, MPEG4 and M-JPEG Dual/Triple Streaming	
	Audio Streaming	NA	
	Users	Support 9 Users	
	Security	ID/Password Protection	
	Alarm Trigger	NA	
	Multicast	Support Multicast Function	
<b>General</b>	Connector	RJ45, DC Power, BNC, Reset Button	
	Automatic IRIS ; Connector	NA	
	Lens Mount	Built-in Varifocal Lens	
	Lens, Angle of View (H)	f2.8~12mm/F1.4/93°~28.7° Megapixel Varifocal Lens	
	Water Resistance	IP66	
	Max. Breaking Strength	NA	
	Power Supply ; Consumption	12Vdc ; 9W	
	Operation ; Storage Temp.	-10°C ~ 50°C ; -20°C ~ 60°C	
	Operation ; Storage Humidity	Maximum: RH80% ; RH90%	
	Dimensions	119(DIA)x88(H)mm	
Net Weight	700g		
Accessories Option	NA		



### Dimensions



UNIT : mm / TOL : ±0.5



\*Specifications are unfixed and do not apply to customized projects. 130121